

Spectrocam measurements of Carl Schofield's step wedges

<b>Epson 2200 with Matte Black ink on EAM</b>				
	Visual	C	M	Y
100%	1.73	1.70	1.78	1.74
95%	1.58	1.56	1.60	1.62
90%	1.48	1.46	1.50	1.51
85%	1.29	1.27	1.30	1.28
80%	1.14	1.12	1.16	1.12
75%	1.02	1.00	1.04	0.97
70%	0.91	0.90	0.94	0.86
65%	0.83	0.80	0.86	0.77
60%	0.74	0.71	0.77	0.68
55%	0.66	0.63	0.70	0.58
50%	0.59	0.57	0.63	0.52
45%	0.53	0.50	0.56	0.46
40%	0.47	0.44	0.50	0.41
35%	0.41	0.38	0.43	0.34
30%	0.35	0.33	0.38	0.28
25%	0.29	0.28	0.31	0.23
20%	0.24	0.23	0.25	0.17
15%	0.19	0.18	0.20	0.12
10%	0.15	0.14	0.15	0.09
5%	0.11	0.10	0.11	0.04
0%	0.06	0.06	0.06	-0.01

<b>Epson 1270, MIS-VM, NCA-nc1 Curve on EAM</b>				
	Visual	C	M	Y
100%	1.67	1.66	1.68	1.72
95%	1.64	1.64	1.64	1.65
90%	1.55	1.55	1.56	1.52
85%	1.44	1.45	1.44	1.43
80%	1.31	1.31	1.32	1.29
75%	1.22	1.22	1.21	1.21
70%	1.12	1.12	1.12	1.09
65%	1.02	1.02	1.01	1.00
60%	0.92	0.92	0.91	0.90
55%	0.84	0.84	0.84	0.82
50%	0.75	0.74	0.74	0.72
45%	0.64	0.64	0.64	0.62
40%	0.56	0.56	0.56	0.53
35%	0.48	0.49	0.48	0.44
30%	0.41	0.41	0.40	0.36
25%	0.34	0.34	0.33	0.28
20%	0.28	0.28	0.27	0.22
15%	0.22	0.23	0.22	0.16
10%	0.17	0.17	0.16	0.10
5%	0.11	0.12	0.11	0.05
0%	0.06	0.06	0.05	-0.01